## METHOD AND APPARATUS FOR DETECTING HYBRIDIZATION REACTION

**Publication number:** JP2001255328 **Publication date:** 2001-09-21

Inventor: NAKAO SUNAO; YAMAMOTO KENJI; YOSHII JUNJI; MIZUNO KATSUYA

Applicant: HITACHI SOFTWARE ENG

**Classification:** 

- international: G01N31/22; B01L7/00; C12M1/00; C12N15/09; C12Q1/68; G01N21/78; G01N33/53; G01N35/02; G01N37/00; G06T1/00; G01N31/22; B01L7/00; C12M1/00; C12N15/09; C12Q1/68; G01N21/77; G01N33/53; G01N35/02; G01N37/00; G06T1/00;

(IPC1-7): G01N33/566; C12M1/00; C12N15/09; C12Q1/68; G01N21/78; G01N31/22; G01N33/53; G01N35/02; G06T1/00

- European: B01L7/00D; C12Q1/68B10A
Application number: JP20000067684 20000310
Priority number(s): JP20000067684 20000310

## Also published as:


EP1132485 (A2) US6589740 (B2) US2002022226 (A1) EP1132485 (A3) EP1132485 (B1)

more >>

## Report a data error here

## Abstract of JP2001255328

PROBLEM TO BE SOLVED: To detect and determinate only a specific bond due to hybridization. SOLUTION: A biochip 10, on which a large number of probe biopolymers are spotted, is housed in a container 20 and a washing liquid is allowed to flow from an infusion device 23. The temperature of the biochip is controlled according to a predetermined time pattern by a heat block 31 and the image of the spotted surface of the biochip is picked up at a determined time interval by an image pickup means 55. A plurality of images picked up by the image pickup means are stored in a computer 40 and analyzed with respect to individual spots to detect hybridization with respect to all of spots with high reliability without receiving the effect of the optimum temperature of hybridization different at every spot corresponding to the kind of a probe.



Data supplied from the *esp@cenet* database - Worldwide

1 of 1 2/8/2008 5:58 PM